



EDF-224J

Ethylene Vinyl Acetate Copolymer

MELT - 2.0

DENSITY - 0.924

EDF-224J is a certified prime grade 5% ETHYLENE VINYL ACETATE (EVA) copolymer designed for production of specialty Blown films requiring excellent balance of mechanical and optical properties. **EDF-224J** films exhibit outstanding clarity, good toughness and impact strength, and superior sealability. **EDF-224J** contains No slip and High antiblock. **EDF-224J** complies with FDA regulation 21CFR 177.1350 concerning the EVA copolymers in contact with food articles.

Features:

- Broad seal range
- Copolymer
- Good impact resistance
- Good toughness
- High antiblocking
- High clarity

For Applications Requiring:

- Form-Fill-Seal packaging
- Ice bags
- Frozen food
- Poultry bags
- Cling wrap

PROPERTIES	ASTM	UNIT	VALUES	
PHYSICAL				
Density	D1505	g/cm ³	0.924	
Melt Flow Rate (190°C, 2.16 kg)	D1238	g/10 min	2.0	
BLOWN FILMS			MD	TD
Secant Modulus - 1% Secant (1.5 mil)	D882	psi	18400	21200
Tensile Strength (Break, 1.5mil)	D882	psi	3640	3470
Tensile Elongation (Break, 1.5 mil)	D882	%	190	590
Elmendorf Tear Strength (1.5 mil)	D1922	g	160	75
Dart Drop Impact	D1709A	g	170	
Haze	D1003	%	4.0	
Gloss (45°, 1.5 mil)	D2457		74	
Film Thickness - Tested		mil	1.5	

The technical information, suggested uses and applications presented are made without charge and are believed to be reliable; however, the Ravago Group* disclaims responsibility for reliance and results of use of this information. THE RAVAGO GROUP DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT(S) DESCRIBED HEREINABOVE, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The Ravago Group expressly disclaims any statements or suggestions as being inducement. All users should rely upon their own knowledge and testing in determining product suitability.